

We bring innovation to transportation.

Carbon Fiber Composite Cable in Prestressed Piles and Beams in Virginia

AASHTO Innovation Initiative Meeting March 2015

Stephen R. Sharp, Ph.D., PE.

Senior Research Scientist

and H. Celik Ozyildirim, Ph.D., PE. Principal Research Scientist

Carbon Fiber Reinforced Polymer (CFRP) Applications

- More than 130 applications by 2009
- Prestressed and Post-tensioning
- Suspension Bridge Main Cable
- Ground Anchor
- Stay Cable



Michigan Post Tensioned



Maine Cable Stayed



CFRP Materials



- Directionally Strong
- Lightweight
- Corrosion Free



3

World's First Bridge Using CFRP





Initial Bridge (20 yrs service)



Replacement Bridge (20 yrs service)



- Shinmiya Bridge
 - Coastal Structure
 - Replacement built in 1988
 - Underside of deck corrosion free



Improvements at VDOT



- VDOT has improved the corrosion resistance of steel reinforced bridge decks using CRR
- Are there other areas of the structure we should look at?



5

Corrosion Damaged Bridges



One of the leading causes of bridge deterioration is corrosion of the steel.

In 2004, FHWA reported \$10.5 billion in bridge rehabilitation

Initial Research Plan

- 18 piles would be fabricated using carbon fiber composite cable reinforcement in place of traditional steel strand and spiral
- Each pile would have16 strands 0.6 in diameter CFRP



VDOT's First Application



VDOT Nimmo Parkway in Virginia Beach



Pile Fabrication

- Bayshore Concrete Products fabricated all the piles
 - Two test piles would be fabricated at facility in Cape Charles, VA
 - Remaining production piles would be fabricated at facility in Chesapeake, VA



Overview of Casting Areas



180-ft (Cape Charles) and 320-ft (Chesapeake) long beds with steam curing pipes at both plants 10



The Coupler (AKA. Double Chuck)



 Several parts required to properly assemble coupler





CFRP Details

- Plastic Tie
- Circular Spiral

 Removable Lift Device





Stressing



Stressed •5 kips •15 kips •25 kips •34 kips



Concrete Placement and Consolidation



Rubber tipped vibrator ends



CFRP Pile Concrete Placed and Cured

Steam Curing

Pile Removed From Forms



Piles are Transported to Site



17

Preparing Piles for Driving



- Piles are lifted and positioned for driving
- During Driving
 - Ram Weight
 - 10,141 lbs
 - Hammer Stroke
 - 5.7 9.2 ft
- Test piles were instrumented

CFRP Reinforced Piles Summary

- Success in fabrication and driving
 - 2 test piles fabricated In Nov 2012 and driven in Oct 2013
 - 16 production piles fabricated in Nov 2013 and driven in Dec 2013
 - Driving response similar to steel reinforced pile

Successful Pile Design

- 24 inch square pile, with 5.7- mm (0.225in) CFRP spiral in a circular pattern
- 16 15.2-mm (0.6-in) strand/pile at 34 kips/strand



CFRP Reinforced Pile Parting Thoughts

- Unlike steel strands
 - Strand cost per foot higher
 - Preparing strands for tensioning is slower
 - No Buy America requirement
 - Corrosion free



What's Next?

Route 49 over Aaron's Creek CFRP Beams

- 2 span bridge
- 4 beams per span
- 82-ft length beam



Aaron's Creek CFRP Beams



 Each beam is a 45" modified bulb tee girders

END VIEW For dimensions not shown, see Typical Beam Section. Indicates strand to receive full prestressing O Indicates strand to receive 5 kips prestressing

22

Current Challenges

Industry

- More competitors
- Eliminating delays in bid response
- Minimize shipping issues
- Use of SCC mixes to reduce need for vibrator

Research

- Temperature or coupler slippage concern
- Improvements to end preparation time
- Maximizing material use to reduce cost

• DOTs

 Define were higher cost AND higher benefit materials could be of value to the DOT and public



We bring innovation to transportation.

Carbon Fiber Composite Cable in Prestressed Piles and Beams in Virginia

Acknowledgements: Ethan Bradshaw, William Ordel, Jonathon Tanks, as well as VDOT Structure and Bridge and VDOT Materials Divisions, and VDOT Lynchburg and VDOT Hampton Roads Districts

Contacts: Celik Ozyildirim: <u>celik@vdot.virginia.gov</u> Steve Sharp: <u>stephen.sharp@vdot.virginia.gov</u>